

# Thermoplastic Exit Sign

# **Series Features**



- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC) 1.7 Watts Standard



- Light-Emitting Diodes 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output



- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- · White or Black Finish
- Easy Installation
- UL Listed
- Flame-Retardant, High-Impact, Thermoplastic Housing
- Damp Location

# **Additional Features**



- Integrated Solid State System
- · Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity



- Increased LED Brightness Level in Emergency Mode
- 2EXKL: (2) 6W Adjustable Lamp Heads



- EXKL: Sealed Nickel Cadmium Battery
- 10-Year Battery Warranty
- 2EXKL: Sealed Lead Calcium Battery
- 5-Year Battery Warranty



- Test Switch
- LED (Power On) Indicator





#### Dimensions

Height: 8.75" Width: 12.75" Depth: 2.5"

### **Ordering Information:**

#### **Series**

XKL - AC Only EXKL - Battery Backup

### # of Sides

2

\*this sign can be single or double sided

#### **Letter Color**

R - Red

G - Green

### **Housing Color**

WWU - White BBU - Black

#### **Optional Features**

- -SD (Self Diagnostic)
- -P2 (Cord & Plug)

ExitSignage.com

(866) 697-9560